

SAFETY DATA SHEET

SECTION 1 — CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

OLOTION 1 OTILIVIO	(L 1 (O			,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		
Product Identifier				[Canada WHMIS Classification]		
Vermiculite (All Grades)				Not Applicable		
Product Use						
Insulating aggregate, Soil conditioner, Low density filler, Abso			ent, Construction Aggre	gate, etc	•	
Manufacturer's Name			Supplier's Name			
P.V.P. Industries Inc.						
Street Address		Street Address				
P.O. Box 129, 9819 Penniman Road						
City		State/Province	City			State/Province
North Bloomfield		OH				
Postal Code Emergency Telephone		ephone	Postal Code		Emergency Te	elephone
44450 440-685-4701						
Date SDS Revised		SDS Prepared By		Phone Num	nber	
February 15, 2024		Michael Dunlavey		440-685	5-4701	
		_	_		<u> </u>	

SECTION 2 — HAZARDS IDENTIFICATION

Route of Entry	Skin Contact	☐ Skin Absorption	Eye Contact		☐Ingestion
Emergency Overvie	W				
Not Hazardous per GHS Criteria.					
Dusts may cause mechanical irritation of eyes, skin, mucous membranes, and respiratory tract. Wear appropriate personal protective equipment. Keep individuals not involved in the cleanup out of the area. Pick up released product with appropriate implements					

protective equipment. Keep individuals not involved in the cleanup out of the area. Pick up released product with appropriate implements and return to original container if reusable. If not reusable, place in appropriate containers for disposal. Although the product itself is non-hazardous, material collected during clean-up operations may be contaminated and should be treated as hazardous unless specific testing, including TCLP, shows the collected material to be non-hazardous. Product is inert and is not expected to present an environmental hazard.

WHMIS Symbols

Not Regulated (Canada)

Potential Health Effects

No specific long term health effects have been identified for asbestos-free vermiculite. As is true of all nuisance or inert particulates, inhalation of high concentrations of dusts and/or particulates over prolonged periods of time may cause a benign pneumoconiosis.

Prolonged or repeated exposure to (respirable) crystalline silica (quartz), which is either not detected or identified at levels below the reporting threshold of 0.1%, may cause a progressive, disabling lung disorder (silicosis). Symptoms may include, cough, shortness of breath, wheezing, decrease in pulmonary function, and recurring non-specific pulmonary illness. The onset of symptoms, except in cases of massive exposures, is usually gradual over a period of several years and is accompanied by changes in the x-ray picture of lungs. Crystalline silica is listed as a known human carcinogen (Group 1) by the International Agency for Research on Cancer (IARC) and as a substance that is known to cause cancer in humans by the National Toxicology Program.

Pre-existing lung and skin conditions may possibly be aggravated by exposure to the components of the product.

SECTION 3 — COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	%	LD ₅₀	CAS#	OSHA PEL-TWA (8- hour), (mg/m³)	ACGIH TLV-TWA (8-hour), recommended, (mg/m³)
Vermiculite (Magnesium Aluminum Iron Silicate)	>98	>2,000 mg/kg (rat)	1318-00-9	5, (respirable fraction) 15, (total dust)	3, (respirable fraction) 10, (total dust)

SECTION 4 — FIRST AID MEASURES

Skin Contact

Wash thoroughly with mild soap and water. Seek medical attention if irritation develops. Remove any contaminated clothing and launder thoroughly before reuse.

Eve Contact

Flush with tepid water for at least 20 minutes holding the eyelids wide open. Seek medical attention if irritation develops.

Inhalation

Remove exposed person to fresh air. If breathing is difficult, oxygen may be administered. If breathing has stopped, artificial respiration should be started immediately. Seek medical attention.

Ingestion

Not expected to be an important route of entry into the body. If large amounts of the product are ingested, seek medical attention.

SECTION 5 — FIRE FIGHTING MEASURES

Flammable	If yes, under which conditions?				
□ _{Yes} ⊠ _{No}					
Means of Extinction					
Use extinguishing media appropriate for su	urrounding material.				
Flashpoint (° C) and Method	Upper Flammable Limit (% by volume)	Lower Flammable Limit (% by volume)			
Not Available	Not Available	Not Available			
Auto ignition Temperature (°C)	Explosion Data — Sensitivity to Impact	Explosion Data — Sensitivity to Static Discharge			
Not Available	Not Available	Not Available			
Hazardous Combustion Products					
Not Available					
NFPA					
Health: 1, Flammability: 0, Reactivity: 0, Other: None					

SECTION 6 — ACCIDENTAL RELEASE MEASURES

Pick up released product with appropriate implements and return to original container if reusable. If not reusable, place in appropriate containers for disposal. Appropriate personal protective equipment cited in Section 8 should be worn during all clean up operations. Although the product itself is non-hazardous, material collected during clean up operations may be contaminated and should be treated as hazardous unless specific testing, including TCLP, shows the collected material to be non-hazardous.

SECTION 7 — HANDLING AND STORAGE

Handling Procedures and Equipment

Appropriate personal protective equipment cited in Section 8 should be worn during handling. Wet mopping or vacuuming with a unit that contains a HEPA filter is recommended to clean up any dusts that may be generated during handling and processing. See also section 6. Wash hands and face thoroughly before eating, drinking or smoking.

Storage Requirements

Do not store with or near incompatible materials cited in Section 10. Store in tightly closed containers out of contact with the environment. Good housekeeping and engineering practices should be employed to prevent the generation and accumulation of dusts.

SECTION 8 — EXPOSURE CONTROL / PERSONAL PROTECTION

Exposure Limits	TLV OSHA PEL	Other (specify	<i>(</i>)			
Specific Engineering Controls (such as ventilation, enclosed process)						
Local exhaust ventilation should be provided to maintain exposures below the limits recommended for nuisance particulates of 10 mg/m³ for total particulates and 3 mg/m³ for respirable particulates. Design details for local exhaust ventilation systems may be found in the latest edition of "Industrial Ventilation: A manual of Recommended Practices" published by the ACGIH Committee on Industrial Ventilation, P.O. Box 16153 Lansing, MI 48910. The need for local exhaust ventilation should be evaluated by a professional industrial hygienist. Local exhaust ventilation systems should be designed by a professional engineer.						
\square	\bowtie	\bowtie	П	\bowtie	П	
Personal Protective Equipment Gloves	Respirator	Eye	Footwear	Clothing	Other	
If checked, please specify type				<u> </u>		
Gloves: Polymeric gloves are re recommended.	commended to prev	ent possible irritat	ion. PVC or simil	ar construction	n materials are	
above, use, as a minimum, a NI matter with an exposure limit of consult your respiratory protecti	Respirator: If dusts or particulates are generated during handling or processing and exposures may exceed the limits cited above, use, as a minimum, a NIOSH approved half mask respirator with cartridges (N95, e.g.) approved for particulate matter with an exposure limit of not less than 0.05 mg/m³. If exposures may exceed 10 times the limit cited in Section 3, consult your respiratory protective equipment supplier or a professional industrial hygienist for selection of the proper equipment. The evaluation of the need for respiratory protection should be made by a professional industrial hygienist.					
Eye: Chemical protective goggle glasses with side shields are re-			e possibility of ey	e contact with	the product. Safety	
Clothing: A polymeric coated apron or other body covering is recommended where there is a possibility if regular work clothing becoming contaminated with the product. All soiled or dirty clothing and personal protective equipment should be thoroughly cleaned and reuse.						
SECTION 9 — PHYSICAL AND CHEMICAL PROPERTIES						
Physical State	Odor and Appearance Odor Threshold (ppm)					
Solid	Odorless tan/brown Flakes, Granules, or Powder None					
Specific Gravity (Bulk) 4-9 lbs/cu.ft.	N/A	Vapor Density (air = 1) Vapor Pressure (mmHg) N/A N/A			mmHg)	
Evaporation Rate	Boiling Point (° C)			Freezing Point (°	C)	
N/A	Not Determined			N/A	,	
рН	Coefficient of Water/Oil Distribution [Solubility in Water]			er]		
Neutral	Neutral N/A <1 %					
SECTION 10 — STABILITY AND REACTIVITY						
Chemical Stability Yes	No If no, under whi	ch conditions?				
Incompatibility with Other Substances Yes No No If yes, which ones? Hydrofluoric acid, halogenated oxidizing agents.						
Reactivity and under what conditions?						
Reacts with hydrofluoric acid to form toxic silicon hexafluoride gas. Do not store in a closed container with halogenated oxidizing agents.						
Hazardous Decomposition Products						
Silicon hexafluoride						

SECTION 11 — TOXICOLOGICAL INFORMATION

Effects of Acute Exposure

Eye contact may cause mechanical irritations if exposed to excessive amount of vermiculite. Skin contact may aggravate existing dermatitis. Inhalation from prolonged and continuous exposure may aggravate existing asthmatic or respiratory conditions.

Effects of chronic exposure

Prolonged inhalation of excessive levels of vermiculite dust may cause a simple pneumoconiotic condition, not normally associated with a decrement in lung function. In cases of long-term exposure to extremely high levels of dust, more serious lung function deterioration may occur.

Irritancy of Product

Mechanical only	
-----------------	--

,	
Skin sensitization	Respiratory sensitization
N/A	N/A
Carcinogenicity-IARC	Carcinogenicity - ACGIH
N/A	N/A
Reproductive toxicity	Teratogenicity
N/A	N/A
Embryotoxicity	Mutagenicity
N/A	N/A
Name of synergistic products/effects	<u>.</u>

N/A

SECTION 12 — ECOLOGICAL INFORMATION

Aquatic Toxicity

In vitro ecotoxicity studies conducted on aqueous extracts of the product under the auspices of the South African Department of Water Affairs and Forestry in 1998 indicated that the product most probably is not toxic to the environment. In each of the ecotoxicity tests cited below, 50 grams of the product were extracted with a liter of distilled water. The resulting solution was used to derive the toxicity parameters.

The 48-hour EC₀ and EC₅₀ (*Daphnia pulex* lethality) were determined to be >50 milligrams of extract per liter (mg/l).

The 72-hour EC₀ and EC₅₀ (algal, Selenastrum capricornutum, growth inhibition) were determined to be >50 mg/l.

The 72-hour EC₀ and EC₅₀ (bacterial, *Pseudomonas putida*, growth inhibition) were determined to be >50 mg/l.

The 48-hour EC₀ and EC₅₀ (frog, *Xenopus laevis*, embryo lethality) were determined to be >50 mg/l.

SECTION 13 — DISPOSAL CONSIDERATIONS

As prepared, the product is considered non-hazardous. Dispose in an EPA approved landfill in accordance with all local, state and federal regulations. If contaminated used or waste product is disposed of, testing, including TCLP, should be conducted to determine hazard characteristics. Empty containers will contain product residues. Observe proper safety and handling precautions. Do not allow empty containers or packaging to be used for any purpose except to store and ship original product.



SECTION 14 — TRANSPORT INFORMATION

Special Shipping Information					
Not currently regulated under Department of Transportation regulations.					
Product Identification Number					
		N/A			
TDG	DOT				
N/A	N/A				
IMO	ICAO				
N/A	N/A				

SECTION 15 — REGULATORY INFORMATION

OLOTION TO TREGOLATION IN ORWINITION				
WHMIS Classification	OSHA			
Not Controlled	29 CFR 1910.1000 TABLE Z-3; Nuisance Dust			
SARA Title III, Sections 302, 313	TSCA			
No components are subject to the reporting levels or requirements Not Listed (Exempt as naturally occurring material)				
This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.				

SECTION 16 — OTHER INFORMATION

Notice: This information relates only to the material designated and may not be valid for such material used in combination with any other materials or in any process. All statements, information and data provided are believed to be accurate and reliable, but are presented without any guarantee, representation, warranty or responsibility of any kind, expressed or implied. Any and all representations and/or warranties of merchantability of fitness for a particular purpose are specifically disclaimed. Users should make their own investigations as to the suitability of the information or product for their particular purpose. Nothing in this document is intended as permission, inducement or recommendation to violate any laws or practice any invention covered by existing patents, copyrights or inventions. P.V.P. Industries Inc. does not accept liability for any loss or damage that may occur from the use of this information.